



Wireless RF Homcloud roller shutter detector

Features

The shutter / garage sensor is a magnetic sensor with an opening / closing frequency detector that detects an integrated digital sensor with very low energy consumption. It has a 12V 23A replaceable battery.

Homcloud code: WL-RFRSS

Model n°: WL-55W

Pilot lamp

LED lamp flash one time: alarm

Installation

Installation location need to be clean and smooth. Place them on border of garage door you want to control. Pay attention because part with transmitter need to be placed on fixed part and not on the shutter.

Fix with bi-adhesive both magnetic part of the sensor. Distance between two parts need to be around 3.5 cm. Open the antenna for best reception

Don't install two detectors in same place to avoid interference with each other.

Test

A. Finished installing, check the batteries are charged, bring the two parts of the sensor closer together until led blinks.

Configuration

1. (recommended) For the complete configuration of the sensors read the manual of the Homcloud Alarm Controller.

When you have inserted the batteries and the sensor has the LED light on, enter the App in the Homcloud Alarm Control Unit already configured and select the "Add Detectors / Sensors" section, then subsequently:

Method A: Move the two magnetic parts of the sensor closer and further away from each other

The LED light will flash again, a beep will sound (control unit) and the sensor will appear on the App ready to be positioned within a zone or room.

Technical parameters

- ◆ Working distance: < 35mm
- ◆ Battery type: Alkaline battery (12V23A battery)
- ◆ Emitting frequency: 433MHz
- ◆ Emitting distance: 150m (open area)
- ◆ Programme code: 1527
- ◆ Case Material: ABS & Iron

More info www.homcloud.com

Imported by: Life365 Italy S.p.A. - European General Agency

Viale Roma 49/a, 47122 Forlì, Italy - Made in China

